

A-1 Wire Tech, Inc.
 4550 Kishwaukee Street FAX: (815) 226-0537
 Rockford, IL 61109 PH: (800) 426-6380
 www: <http://www.a-1wire.com>



A-1 Wire Tech, Inc.

A Special Metals Company

Material Safety Data Sheet

SECTION 1 - PRODUCT IDENTIFICATION

Product Type: Welding Wire
 Product Name: L605
 Specification: AMS 5796 and AMS 5797
 Manufacturer: Huntington Alloys
 3200 Riverside Dr
 Huntington, WV 25705
 800-334-4626
 Date Prepared 08/03/2001

SECTION 2 - HAZARDOUS INGREDIENTS

IMPORTANT! This section covers the material from which these products are manufactured. Fumes and gases produced when welding with normal use of these products are covered in Section 5.

Components	CAS No.	OSHA PEL (mg/m ³)	ACGIH TLV (mg/m ³)	Wt. %
Nickel	7440-02-0	1.0	1.5 ¹	10.0
Cobalt	7440-48-4	0.1	0.02	balance
Iron	1309-37-1	10.0	5.0	3.0*
Chromium	7440-47-3	1.0	0.5	20.0
Tungsten	7440-33-7	none	5.0	15.0
Silicon	7440-21-3	15.0 dust, 5.0 resp.	10.0	1.0*
Manganese	7439-96-5	none	0.2	1.5
Carbon	1333-86-4	3.5	3.5	0.10

¹ Subject to reporting requirements of Section 313 of the Emergency Planning & Community Right-to-Know Act of 1986 (SARA) and 40 CFR Part 372. ² * - Maximum

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

Solid Wire, Odorless, Insoluble, Silver in appearance

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

(Nonflammable)

Thermal spray and welding arcs and sparks can ignite combustibles and flammables. Refer to American National Standard Z49.1 for fire prevention during the use of welding and allied procedures.

NFPA NUMERICAL CODES: Health Hazard 0 Fire Hazard 1 Reactivity Hazard 0

SECTION 5 - REACTIVITY DATA

Arc fumes and gases cannot be classified simply. The composition and quantity of both are dependent upon the sprayed, the process, procedure and materials used. Other conditions which also influence the composition and quantity of the fumes and gases to which workers may be exposed include: coatings on the metal sprayed (such as paint, plating, or galvanizing), the number of arc spray units and the volume of work area, the quality and amount of ventilation, the position of the operator's head with respect to the fume plume, as well as the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from cleaning and degreasing activities).

When the material is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 2. Fume and gas decomposition products, and not the ingredients in the material, are important. The concentration of a given fume or gas component may decrease or increase by many times the original concentration in the material. Also, new compounds not in the electrodes may form. Decomposition products of normal operation include those originating from the volatilization, reaction, or oxidation of the materials shown in Section 2, plus those form the base metal and coatings, etc., as noted above. Reasonably expected decomposition products from normal use of these products include a complex of the oxides of the materials listed in Section 2, as well as carbon monoxide, carbon dioxide, ozone and nitrogen oxides. The fume limit for chromium and nickel may be reached before the general limit for welding fumes (5 mg/m³) is reached.

One recommended way to determine the composition and quantity of fumes and gases to which workers are exposed is to take an air sample inside the operator's helmet if worn or in the worker's breathing zone.

A-1 Wire Tech, Inc.

4550 Kishwaukee Street FAX: (815) 226-0537
Rockford, IL 61109 PH: (800) 426-6380
www: <http://www.a-1wire.com>



A-1 Wire Tech, Inc.

A Special Metals Company

Material Safety Data Sheet

See ANSI/AWS F1.1 "Method for Sampling Airborne Particles Generated by Welding and Allied Processes" and "Characterization of Arc Welding Fume" available from the American Welding Society, 550 N.W. LeJeune Road, Miami, FL 33126

SECTION 6 – HEALTH HAZARD DATA

Electric arc welding or oxyfuel welding may create one or more of the following health hazards:

ARC RAYS can injure eyes and burn skin.

HEAT RAYS (infrared radiation) from flame or hot metal can injure eyes.

ELECTRIC SHOCK can KILL.

NOISE can damage hearing.

CARCINOGENICITY Chromium, nickel, cobalt, and their compounds are on the IARC and NTP lists as posing a carcinogenic risk to humans.

EMERGENCY AND FIRST AID PROCEDURES – Call for medical aid. Employ first aid techniques recommended by the American Red Cross.

SHIELDING GASES such as argon, helium and carbon dioxide are asphyxiates and adequate ventilation must be provided.

FUMES AND GASES can be dangerous to your health. **COMMON ENTRY IS BY INHALATION.**

SHORT TERM (ACUTE) – overexposure to welding fumes may result in discomfort such as dizziness, nausea, or dryness or irritation of nose, throat, or eyes.

Chromates present in the fume can cause irritation of the respiratory system, damage to lungs and asthma like symptoms. Nickel compounds in the fume can cause a metallic taste, nausea, tightness in the chest, fever and allergic reactions.

LONG TERM (CHRONIC) – overexposure to welding fumes can lead to siderosis (iron deposits in the lung) and affect pulmonary function.

Chromium VI compounds are required by OSHA to be considered carcinogenic. Long term exposure to Chromium and Chromium III Oxide dust can cause scaling, redness, itchiness, and a burning sensation on the skin. Long term overexposure to nickel compounds may cause lung fibrosis or pneumoconiosis. Soreness and itchiness of the nose and change in skin color and/or appearance may also result. Nickel and its compounds are required to be considered as carcinogenic by OSHA.

THRESHOLD LIMIT VALUE - The ACGIH 1996-97 recommended limit for welding fumes not otherwise classified (NOC) is 5mg/m³. TLV-TWA's should be used as a guide in the control of health hazards and not as fine lines between safe and dangerous concentrations. See Section 5 for specific fume constituents which may modify this TLV-TWA.

SECTION 7 – PRECAUTIONS FOR SAFE HANDLING & USE/APPLICABLE CONTROL MEASURES

Read and understand the manufacturer's instructions and the precautionary label on the product. See American National Standard Z49.1, "Safety in Welding, Cutting, and Allied Processes", published by the American Welding Society, 550 N.W. LeJeune Road, Miami, FL 33126 and OSHA Publication 2206 (29CFR1910), US Government Printing Office, Washington, D.C. 20402 for more detail on many of the following.

VENTILATION – Use enough ventilation, local exhaust at the arc, or both, to keep the fumes and gases below TLV's in the worker's breathing zone and the general area. Train the operator to keep his head out of the fumes.

RESPIRATORY PROTECTION – Use respirable fume respirator or air supplied respirator when spraying in confined space or where local exhaust or ventilation does not keep exposure below TLV.

EYE PROTECTION – Wear helmet or use face shield with filter lens. As a rule of thumb, start with a shade that is too dark to see the work piece. Then go to the next lighter shade which gives sufficient view of the work piece. Provide protection screens and flash goggles, if necessary to shield others.

PROTECTIVE CLOTHING – Wear head, hand and body protection which help to prevent injury from radiation, sparks, and electrical shock. See ANSI Z49.1 At a minimum this includes operator's gloves and a protective face shield, and may include aprons, hats shoulder protection, as well as dark substantial clothing. Train the operator not to touch live electrical parts and to insulate himself from work and ground.

PROCEDURE FOR CLEANUP OF SPILL OR LEAKS – Not applicable.

WASTE DISPOSAL METHOD – Prevent waste from contaminating surrounding environment. Discard any product, residue, disposable container or liner in an environmentally acceptable manner, in full compliance with federal state and local regulations.

The information herein is supplied in good faith, but no warranties are expressed or implied.